

FORMULA STUDENT INSPECTION SHEET

ELECTRIC – copy for Formula Student Austria



UNIVERSITY:	Tallinn TU UAS
VEHICLE NUMBER:	24
INSPECTION ORDER:	-
SES PASSED:	✓
IADR PASSED:	✓
-	-
ESF PASSED:	-
TS VOLTAGE:	604.8 V
BODY PROTECTION R:	15 kΩ

Present the vehicle for inspection in the following order:

- Pre-Inspection
- Accumulator Inspection* Su. 9:00 - 10:45
- 1. Electrical Inspection* Mo. 10:00 - 11:30
- Mechanical Inspection* Mo. 12:15 - 13:45 Your Pit 25
- Driver Egress Su. 12:30 - 13:15 Event Tent Campsite
- 2. Tilt Test*
- 3. Rain Test*
- 4. Brake Test*

* the vehicle is marked with a sticker if this part has been passed successfully.

Used Symbols:

- Information
- ▶ Action
- △ Check in responsibility of the team
- Check
- ⊙ Check optional, if Mechanical Inspection at FSA, FSCH, FSN, FSPT is passed

NOTES:

- This form must stay with the push bar at all times!
- Technical inspection approval voids if inspection sheet is lost.
- If there is a conflict between this form and the rules, the rules prevail.

PART I: COMMENTS FROM DOCUMENT REVIEW

ACCUMULATOR

ELECTRICAL

MECHANICAL

FORMULA STUDENT INSPECTION SHEET

ELECTRIC – copy for Formula Student Austria



PART II: DRIVER'S SAFETY INSPECTION

TIRES

- | | |
|---|---|
| 1 <input type="radio"/> DRY TIRES - Make:
_____ | 4 <input type="radio"/> RAIN TIRES - Make:
_____ |
| 2 <input type="radio"/> DRY TIRES - Size:
_____ | 5 <input type="radio"/> RAIN TIRES - Size:
_____ |
| 3 <input type="radio"/> DRY TIRES - Compound:
_____ | 6 <input type="radio"/> RAIN TIRES - Compound:
_____ |
| | 7 <input type="radio"/> RAIN TIRES - 2,4 mm min. tread depth molded by tire manufacturer |

DRIVER GEAR & SAFETY

- | | |
|--|--|
| 8 <input type="radio"/> FIRE EXTINGUISHERS - Two (2) hand-held, 0.9 kg (2 lb.) minimum, dry chemical (10BC, 1A10BC, 34B, 5A 34B, 20BE or 1A 10BE), with pressure/charge gauge, Aqueous Film Forming Foam (AFFF) fire extinguishers are prohibited, 1 WITH VEHICLE securely installed on push-bar, 1 in paddock. (Must see BOTH at inspection.). | 41.1/2020 or newer. FIA 8860-2010, FIA 8860-2018, FIA 8859-2015 or newer. Closed Face, no Open Face, must have integrated shield (no dirtbike helmets). No camera mounts. |
| 9 <input type="radio"/> UNDERWEAR - Nomex or equivalent, fire resistant underwear (no cotton, no polyester, no bare skin). No holes. | 14 <input type="radio"/> FHR/HANS - If used, must be certified to one of these standards: FIA 8858-2010, FIA 8860-2004, SFI 38.1. |
| 10 <input type="radio"/> SOCKS - Nomex or equivalent, fire resistant socks (no cotton, no polyester, no bare skin). No holes. | 15 <input type="radio"/> DRIVER SUITS - Single piece SFI 3.2A/5 (or higher), SFI 3.4/5 (or higher), FIA 8856-2000/2018 (or higher), and LABELED AS SUCH. FIA hologram present. No holes. |
| 11 <input type="radio"/> GLOVES - Fire resistant material. Leather allowed only over fire resistant material. FIA hologram present. No holes. | 16 <input type="radio"/> HAIR COVER - Fire resistant (Nomex or equiv.) balaclava of full helmet skirt REQUIRED FOR ALL DRIVERS. No holes. |
| 12 <input type="radio"/> ARM RESTRAINTS - SFI Standard 3.3 or equivalent. | 17 <input type="radio"/> SHOES - SFI 3.3 or FIA 8856-2000/2018 |
| 13 <input type="radio"/> HELMETS - Snell K2015, K2020, M2015, M2020, SA2020, EA2016 or newer. 31.1/2015, 31.1/2020, 41.1/2015, | 18 <input type="radio"/> SEWING OR STITCHING - Teams must show compliance to T13.3 if driver's clothing is embroidered. Fire resistant material must be used, examples: Nomex, Aramid, Belcotex and Indura. |

CHASSIS & SES & REQUIRED TESTS PRESENTED

- | | |
|---|---|
| 19 <input type="radio"/> SES TUBING & MATERIALS - Team must show an APPROVED SES. No magnesium tubes in primary structure. | mm) and two leg or anti-submarine straps (min. width 50 mm). (7-point system must have three anti-submarine straps). Must be securely attached to prim. structure (25.4 x 2.4 mm or equal.). |
| 20 <input type="radio"/> SES TEST SPECIMEN - Team must show all relevant test specimen. Labeled (non-removable) with structure acronym and date. Specimen width, skin & core thickness according to SES. Check samples SIS V, FBH, FBHS & MHBS | 28 <input type="radio"/> LAP BELT MOUNTING - Pivoting mounting with eye bolts or shoulder bolts attached securely to primary structure. Min. tab thickness 1.6 mm. Attachment brackets to the monocoque must be steel, see T5.3.2. Attachments must be near a frame node, max. 50mm distance. |
| 21 <input type="radio"/> INSPECTION HOLES - 4.5 mm inspection holes required in non-critical areas of front & main hoops. Must be accessible with standard calliper. Laminate has to be removed locally for laminated front hoops. Inspectors may ask for holes in other tubes and/or structures. | 29 <input type="radio"/> SHOULDER HARNESS MOUNTING - Mounting points 180 - 230 mm apart (measured center to center). Attach to primary structure - 25.4 x 2.4 mm or 25.0 x 2.5 mm steel tube min. NOT to put bending loads into main hoop bracing without extra bracing. Additional braces if not straight to main hoop. Cannot pass through a firewall. Attachment brackets to the monocoque must be steel. |
| 22 <input type="radio"/> SES DIMENSIONS & THICKNESSES - All chassis dimensions according to SES: tube diameter and wall thickness; laminate skin thickness (max. deviation 0,2 mm), core thickness, panel height (SIS H, FBHS, FHB, MHBS, rear accu protection). | 30 <input type="radio"/> MAIN HOOP - Must be made of one piece and extend to lowest frame member. Above major structure, must be within 10 deg. of vertical plane. Smooth bends without wrinkles, not oval after bending. |
| 23 <input type="radio"/> HOLES & CUTOUTS - All holes/cutouts in primary structure < 60 mm ² or deducted from panel height. Compare cutouts with SES document | 31 <input type="radio"/> MAIN HOOP BRACING - Same material as main hoop (both (non) magnetic). One straight brace on each side. Attached within 160 mm from the top. Min. 30 deg. included angle with main hoop. No bends. No rod-ends. Proper design for removable braces (capping etc.) on both ends. |
| 24 <input type="radio"/> LAMINATE ORIENTATION - Tested structures must be correctly oriented or quasi-isotropic (T3.5.4, especially MHBS). Check laminate transitions. | 32 <input type="radio"/> FRONT HOOP - Must be closed section metal tube. Can be multi-piece with gussets or additional attachments to the monocoque. Must extend down to lowest frame member. No lower than top of steering wheel. Max. 20 deg. to vertical. Check manufacturing documentation for laminated front hoop. |
| 25 <input type="radio"/> BOLTED JOINTS/ATTACHMENTS in primary structure - Distance hole centerline to the nearest free edge > 1.5 x hole diameter. Steel backing plates (≥ 2 mm thick) with perimeter near circular or oval used at attachment points (must be fully supported). According to SES (T3.16.6) if two panels are bolted together. Check rear plates. Check welded tube inserts. | 33 <input type="radio"/> FRONT HOOP BRACING - Two straight forward facing braces, attached within 50 mm of top. Extra rearward bracing required if front hoop leans backwards more than 10 deg. |
| 26 <input type="radio"/> HARNESS ATTACHMENTS for shoulder harness, lap belt and anti-submarine belt according to SES calculation, simulation and/or physical test. Test/calculation conducted according to realistic belt angle. | 34 <input type="radio"/> FRONT BULKHEAD SUPPORT - Upper tube connecting within 50 mm of top of bulkhead, and connecting within 100 mm above and 50 mm below upper SIS tube. Check sharp |
| 27 <input type="radio"/> DRIVER RESTRAINT HARNESS - SFI 16.1, SFI 16.5, SFI 16.6, FIA 8853/2016. 6- or 7-point system – Two-piece lap belt (min. width 50 mm), two shoulder straps (min. width 75 | |

FORMULA STUDENT INSPECTION SHEET

ELECTRIC – copy for Formula Student Austria



transitions in loadpath

- 35 ○ **SIDE IMPACT PROTECTION** - Upper tube between 240 - 320 mm above lowest inside chassis point between FH and MH.

- 36 ○ **SUSPENSION PICK-UP POINTS** - Inspected thoroughly for integrity. No crushed core, no skin detached from core (check with knocking method).

IAD & REQUIRED TESTS PRESENTED

- 37 ○ **FRONT IMPACT PROTECTION** - Team must show an APPROVED IAD and test piece (if applicable), which both must reflect status on the car. IMPACT ATTENUATOR forward of bulkhead. IA must be securely fastened directly to AIP capable of taking transverse & vertical loads (no tape, etc.). Adhesive strength 24 MPa. Non-crushable objects forward of bulkhead must have been evaluated in IAD. Front wing and their supports must be in accordance with approved IAD. No wing supports through the IA.
- 38 ○ **CRASH TEST (if applicable)** - If a crash test was needed to comply with the rules, the test fixture must be representative of the actual car. At least 50 mm clearance behind the AIP. Maximum permanent deflection of AIP 25 mm. IA attachment must remain working condition.

- 39 ○ **IAD DIMENSIONS** - IA min. 200 mm long x 200 mm wide x 100 mm high. AIP solid sheet metal, min. 1.5 mm steel or 4.0 mm aluminium; alternative design accepted, if SES/IAD approved. Standard IA without testing: Requires diagonal or X-brace if FBH dimensions larger than 400 mm width and/or 350 mm height.
- 40 △ **IA POSITION** - The minimum volume dimensions cannot not be more than 350 mm above ground (measured with driver seated).
- 41 ○ **AIP ATTACHMENT** - Standard: must be welded (full perimeter, size: min. to centerlines) or min. 8 screws M8 grade 8.8 (critical fasteners T10, 2 mm backing plates, edge distance ratio min. 1,5, distance between bolts max. 200 mm). Non-standard: Must follow T3.16.6.

SCRUTINEERING STATUS UPDATE

- ▶ Set online scrutineering status to *Passed* or *Failed*

NON-COMPLIANCE / COMMENTS

APPROVAL

Inspector Names	Date, Time	Signatures when passed
1. _____ / _____	_____	_____

PART III: EGRESS TEST

DRIVER POSITION

- 42 **ARM RESTRAINTS**- Must be installed so the driver can release them and exit unassisted regardless of vehicle's position.
- 43 **HEAD RESTRAINT**- Near vertical. Max. 25 mm from helmet. Helmet contact point 50 mm min. from any edge.
- 44 **MAIN HOOP & FRONT HOOP HEIGHTS** - Helmet of driver to be 50 mm below line between top of front and main roll hoop AND between top of main hoop to rear attachment point of main hoop bracing.
- 45 **LAP BELT MOUNTING** - Must pass over pelvic area between 45 - 65 deg. to horizontal for upright driver, 60-80 deg. for reclined. The lap belts must not be routed over the sides of the seat.
- 46 **SHOULDER HARNESS MOUNTING** - Angle from shoulder between 10 deg. up and 20 deg. down to horizontal.

DRIVER EGRESS TEST

- All drivers must be able to exit the vehicle in less than 5s.
- Driver must be seated in ready to race condition.

EGRESS PROCEDURE

- ▶ Both hands on the steering wheel. (in all possible steering positions)
- ▶ Pressing cockpit-mounted shutdown button.
- The egress time will stop when the driver has both feet on the ground

DRIVER APPROVAL & RUN DOCUMENTATION

Driver's Name	Wristband ID	Signature Inspector - when passed	Acc	Skid Pad	AutoX	Endurance
1. _____	_____	_____	<input type="checkbox"/> <input type="checkbox"/>	<input type="checkbox"/> <input type="checkbox"/>	<input type="checkbox"/> <input type="checkbox"/>	<input type="checkbox"/>
2. _____	_____	_____	<input type="checkbox"/> <input type="checkbox"/>	<input type="checkbox"/> <input type="checkbox"/>	<input type="checkbox"/> <input type="checkbox"/>	<input type="checkbox"/>
3. _____	_____	_____	<input type="checkbox"/> <input type="checkbox"/>	<input type="checkbox"/> <input type="checkbox"/>	<input type="checkbox"/> <input type="checkbox"/>	<input type="checkbox"/>
4. _____	_____	_____	<input type="checkbox"/> <input type="checkbox"/>	<input type="checkbox"/> <input type="checkbox"/>	<input type="checkbox"/> <input type="checkbox"/>	<input type="checkbox"/>

Checked by officials only after a dynamic run!

FORMULA STUDENT INSPECTION SHEET

ELECTRIC – copy for Formula Student Austria



PART IV: ACCUMULATOR INSPECTION

The time limit for this part of the inspection is 105 minutes. Continuation of the inspection is possible after requeueing. During technical inspection all work carried out on the accumulator must be approved by a technical inspector.

REQUIRED RESSOURCES

- 47 An ESO must attend.
- All accumulator containers to be used during the event.
 - Accumulator Container Hand Cart.
 - Charger.
 - Tools needed for (dis-)assembly of Accumulator Container.
 - PDF or print-out of rule questions, if necessary.
 - Pictures of accumulator internals, if necessary.
 - Datasheets for used wiring, insulation materials, and TS components. (printed or properly sorted on one laptop, not on a cell phone)
 - Samples of all wire types used inside the accumulator container.
 - Samples of all used accumulator container material.
 - Fully assembled spare boards of all inaccessible TS boards inside the accumulator
 - Laptop and cables to display data of the AMS

SAFETY BRIEFING

- no jewellery, no rings
- no cell phone
- no watch / no necklace
- no sources of distraction
- do not wear synthetic clothes
- wear safety glasses
- wear safety gloves

BASIC SET OF HV-PROOF TOOLS

- 48 Insulated cable shear.
- 49 Insulated screw driver.
- 50 Insulated spanners (n/a if no screwed connections in TS).
- 51 Multimeter with protected probe tips
- 52 two 4mm banana plug test leads (1000V CAT III)

SAFETY EQUIPMENT

- 53 Face shield.
- 54 Safety glasses (minimum three).
- 55 HV insulating gloves (minimum two pairs).
- 56 HV insulating blankets (two) (min $1 m^2$) with label or serial number and datasheet.

SELF DEVELOPED PCBS

- ▶ Ask for fully assembled spare PCB of self developed PCBs inside accumulator container.
- 57 Sufficient spacing regarding system voltage and implementation.
- 58 Sufficient insulation and temperature rating of coating if used, datasheet available.
- 59 Coating process according to datasheet

CHARGER ASSEMBLY

- 60 Completely closed. Check opening in HV/TS enclosures, try to reach HV/TS potentials with insulated test probe (100 mm length, 6 mm diameter).
- 61 Interlock integrated.
- 62 TSMP integrated
- 63 Emergency shutdown button integrated.
- 64 Emergency shutdown button ≥ 24 mm diameter.
- 65 TS wiring is orange, marked with gauge, temperature rating $> 85^\circ C$ and voltage rating.
- 66 Conductive parts of charging equipment and accumulator are connected to protective earth (PE) while charging. Mind new groundign rules, see EV 3.1
- 67 Switches, plugs and indicators must be labeled.

DIS-CHARGE CIRCUIT AND BODY PROTECTION RESISTORS

- ▶ Switch off Charger. Measure resistance between TS+ and TS- measuring points.
- 68 Resistance is $30 k\Omega^1$ + discharge resistor
- 69 Body protection resistor power rating is $> 6.1 W^2$

¹ 2 x Body Protection Resistor (BPR)

² sufficient to short circuit TS+ and TS-

INSULATION MEASUREMENT TEST

- ▶ Check low resistance connection between LV ground MP and PE/casing
- ▶ Choose test voltage to 500 V.³
- ▶ Connect insulation tester to charger TS+ and LV ground.
- ▶ Connect charger (do not activate charger) to accumulator, keep AIRs opened.
- ▶ Measure resistance: $R_{iso+} =$ k Ω
- 70 Resistance is much higher than 315 k Ω ⁴.
- ▶ Connect insulation tester to TS- and LV ground.
- ▶ Measure resistance: $R_{iso-} =$ k Ω
- 71 Resistance is much higher than 315 k Ω ⁴.
- 72 Resistances are nearly equal.
- ▶ Open container housing, remove maintenance plugs.
- ▶ Check if no voltage is present.

ASSEMBLY

- 73 All components and parts of the accumulator container need to be properly fixed.
- 74 SES - All used fasteners must be secured by the use of positive locking except they are non-conductive and non-structural.
- 75 TS potentials are insulated against inner wall of accumulator container if container made from conductive material.
- 76 SES - Tabs of pouch cells must not carry mechanical loads.
- 77 No cells are damaged or can be damaged by the segment structures.
- 78 No soldering in high current path
- 79 Every container contains at least one appropriately sized and rated fuse.
 - ▶ Check datasheet of fuse, main wire and cells and compare to ESF.
- 80 Every container contains at least two appropriately sized and rated isolation relays (current and voltage).
- 81 Isolation relays and fuses are separated from cells by barrier according UL94-V0 or equivalent.
- 82 Pre-charge relay is of mechanical type with appropriate voltage rating.
 - ▶ Check datasheet of pre-charge relay and compare to ESF
- 83 Maintenance plugs are located at both poles of each stack (including first and last stack).
- 84 Maintenance plugs removable without tools.
- 85 Maintenance plugs have positive locking mechanism.
- 86 Maintenance plugs must not be able to unintentionally create circuits or short circuits.
- 87 Stacks separated by Maintenance plugs \leq 120 VDC.
- 88 Stacks separated by Maintenance plugs \leq 6 MJ.
- 89 Stacks are insulated and separated by a fire resistant barrier according to UL94-V0 for min. used thickness or equivalent.
- 90 SES - Holes in container only for wiring harness, ventilation, cooling or fasteners, if mechanical properties are not influenced.
 - ▶ Check opening in TS enclosures, try to reach TS potentials with insulated test probe (100 mm length, 6 mm diameter).
- 91 If fully closed, equalizing valve implemented.
- 92 Spare accumulators of same size, weight and type.

WIRING

- 93 All TS wires have proper overcurrent protection.
- 94 No other wires than TS wires are orange.
- 95 Securely anchored to withstand at least 200 N, if outside of enclosure.
- 96 Located out of the way of possible snagging or damage.
- 97 TS and LV wires separated (not valid for Interlock).
- 98 Every wire used in the Accumulator container (TS and LV) is rated for ≥ 604.8 V⁵.
- 99 Possible to clearly assign and prove gauge, temperature and voltage rating of TS wires.
- 100 Positive locking mechanism or if no positive locking possible, automotive certified components.
 - ▶ Check if insulated tools needed for the assembly of certified components are available
- 101 Insulation is not only insulating tape or rubber-like paint.

INDICATOR LIGHT OR VOLTMETER

- 102 Red indicator light or voltmeter installed
- 103 Marked with "Voltage Indicator"
- 104 Visible while opening the battery connector.
- 105 Hard wired electronics, supplied by TS
- ▶ Connect power supply with 60 VDC⁶ to accumulator TS connector. Use proper plugs, no measuring probes.
- 106 Indicator light on or voltmeter showing present TS voltage.
- 107 Visible in bright sunlight.

ACCUMULATOR MANAGEMENT SYSTEM

- 108 A minimum of 30% of cells are monitored with temperature sensors.
- 109 Every temperature sensor placed on negativ terminal of monitored cell or in <10mm distance on busbar.
 - ▶ Disconnect AMS current sensor connector
- 110 The AMS must open the shutdown circuit within 0.5 s.
 - ▶ Disconnect any other AMS internal connector
- 111 The AMS must open the shutdown circuit within 1 s.
 - ▶ Ask the team to connect their laptop to the AMS.
- ▶ Connect charger to battery/batteries, start charging process.
- 112 Cell voltages can be displayed.
- 113 Cell temperatures can be displayed.
- 114 Plausible accumulator current can be displayed.
 - ▶ Disconnect one SINGLE voltage sense wire, if any wires used.
- 115 The AMS must open the shutdown circuit within 0.5 s.
 - ▶ Disconnect one SINGLE temperature sense wire, if any wires used.
- 116 The AMS must open the shutdown circuit within 1 s.

³ $U_{max} \leq 250 V_{DC}$ $U_{max} > 250 V_{DC}$
 $U_{Test} = 250 V_{DC}$ $U_{Test} = 500 V_{DC}$

⁴ Minimal Resistance = $500 \Omega \cdot V \cdot U_{max} + BPR$

⁵ max. TS voltage

⁶ 60 V or half the nominal tractive system voltage, whichever is lower

FORMULA STUDENT INSPECTION SHEET

ELECTRIC – copy for Formula Student Austria



CHARGER SHUTDOWN CIRCUIT

- 117 IMD is integrated into the charging system
 - ▶ Connect charger to battery/batteries, start charging process
- 118 Voltage indicator shows that HV is present
 - ▶ Press shutdown button
- 119 AIRs open
- 120 Voltage indicator shows voltage <60 V
 - ▶ Start charging, unplug TS accumulator connector
- 121 AIRs open.
- 122 Charger disabled, no voltage at charger connector

INSULATION MONITORING DEVICE

- 123 One IMD ground line is connected to the accumulator container and one ground line is connected to the charger casing by a separate wired connection
 - ▶ $R_{Test} = 120\text{ k}\Omega^7$
 - ▶ Activate charger output, connect R_{Test} between TS+ and LV GND.
- 124 Shutdown circuits opens within 30 s.
- 125 TS voltage decreases below 60 VDC within 5 s after shutdown
- 126 Reactivation of charger output is not possible.
 - ▶ Push the reset button, if any.
- 127 Reactivation of charger output is not possible.
 - ▶ Remove R_{Test} . Wait 40 s until IMD resets status output.
- 128 Reactivation of charger output is not possible.
 - ▶ Activate TS, connect R_{Test} between TS- and LV GND.
- 129 Shutdown circuits opens within 30 s.

ACCUMULATOR CONTAINER

- ▶ SES - Team must show approved SES for accumulator container.
- ▶ SES - Team must show SES test samples for accumulator container if alternative materials are used.
- 130 SES - Accumulator container manufactured according to SES. check material and bonding quality
- 131 SES - Internal vertical walls have to be rigidly fastened to the container. Minimum 75% of the height of the external walls. Divide the accumulator in sections of max. 12 kg.
- 132 SES - Cells securely fastened towards all 3 directions. Form-fitting max. 0,5mm gap.
- 133 SES - All parts carrying cells and loads: UL94-V0 certified materials. Check Datasheet.
- 134 SES - External openings not pointing towards driver or hand cart operator.
- 135 Vehicle number, university name and ESO phone number(s) written on a high contrast background.
- 136 Roman Sans-Serif characters of at least 20 mm high are used.
- 137 Warning stickers with side length of $\geq 100\text{ mm}$ and text "Always Energized" and "High Voltage" (if TS >60 V) installed. (triangle with black lightning bolt on yellow background)
- 138 SES - Check if all parts and the cover/lid of the housing are rigidly fastened.

HAND CART

- 139 Hand cart present with four wheels. Max. dimensions 1200 mm x 800 mm.
- 140 Hand cart has always on type brake system.
- 141 The accumulator must be mechanically fixed to the handcart while on the handcart.
- 142 The accumulator must be protected from vibrations and shocks.
- 143 Firewall (same width as hand cart, from lowest point to 30 cm above TSAC/handle) must protect operator.
- 144 Label according to EV5.3.8 on hand cart firewall below handle.

SEALING OF COMPONENTS

- ▶ After all tests have been passed successfully seal the inspected TS housings:
- 145 Accumulator container(s) including spares
- 146 Charger
- 147 Additional Part:
- 148 Additional Part:

SCRUTINEERING STATUS UPDATE

- ▶ Set online scrutineering status to *Passed* or *Failed*

⁷ $R_{Test} = (\text{max. TS voltage} \cdot 250\text{ Ohm/V}) - \text{BPR}$

FORMULA STUDENT INSPECTION SHEET

ELECTRIC – copy for Formula Student Austria



NON-COMPLIANCE / COMMENTS

APPROVAL

	Inspector Names	Date, Time	Signatures when passed
1.	_____ / _____	_____	_____
2.	_____ / _____	_____	_____

FORMULA STUDENT INSPECTION SHEET

ELECTRIC – copy for Formula Student Austria



PART V: ELECTRICAL INSPECTION

The time limit for this part of the inspection is 105 minutes. Continuation of the inspection is possible after requeuing. During technical inspection all work carried out on the vehicle must be approved by a technical inspector.

REQUIRED RESSOURCES

- 149 An ESO must attend
 - LV battery or cell datasheet
 - For self-developed LV battery packs: an opened battery pack, laptop, and cables to display data of the AMS
 - Laptop and cables to display data of the TS accumulator AMS
 - Datasheets for used wiring, insulation materials, and TS components. (printed or properly sorted on one laptop, not on a cell phone)
 - At least all non-passed parts of the ESF. (printed or properly sorted on one laptop, not on a cell phone)
- Samples of all wire types used for the tractive system
- Fully assembled spare boards of all inaccessible TS boards outside the accumulator
- The connector to safely close the SDC while the HVD is removed
- The connector to safely supply the TS using shrouded receptacles when the TS accumulator is unconnected
- Photographs of all inaccessible TS connections
- "TSAL green" sign

LV BATTERY

- 150 Voltage ≤ 60 VDC
- 151 Rigid and sturdy casing
- 152 Only for wet-cell batteries: IPX7 rated and acid resistant casing if inside cockpit
- 153 Behind Firewall
- 154 Short circuit protection (e.g. fused)
- 155 Grounded to the chassis
- 156 Proper insulation of internal electrical connections
- 157 Proper mounting of cells
- 158 Complete battery pack inside rollover protection envelope
- 159 Following checks only for Li-Ion batteries other than LiFePO₄:
- 160 UL94-V0 for min. used thickness or equivalent casing
- 161 Overcurrent protection that trips below max. discharge current
- 162 Overtemperature protection of at least 30 % of the cells (max. 60°C or datasheet, whichever is lower)
- 163 Voltage protection of all cells
- 164 Signal failures electrically disconnect the LV battery (SCS)
 - ▶ Ask the team to connect their laptop to the AMS
- 165 Cell voltages can be displayed
- 166 Cell temperatures can be displayed

SELF DEVELOPED PCBs

- ▶ Ask for fully assembled spare PCB of self-developed PCBs
- 167 Sufficient spacing regarding system voltage and implementation
- 168 Sufficient insulation and temperature rating of coating if used, datasheet available
- 169 Coating process according to datasheet
- 170 BSPD PCB(s) is standalone with only minimum interface
- 171 BSPD PCB(s) are directly supplied from the LVMS
- 172 Ends of a BSPD current transducer's auxiliary winding must be insulated.

MASTER SWITCHES

- 173 TSMS & LVMS installed easily accessible on the right side of the vehicle and located next to each other
- 174 All master switches are located above 80% of shoulder height of Percy
- 175 Rigidly mounted and no need to be removed during maintenance
- 176 Rotary type with removable handle
- 177 Handle length ≥ 50 mm
- 178 "ON" position in horizontal
- 179 "ON" and "OFF" positions marked
- 180 TSMS with locking mechanism for "OFF" position
- 181 LVMS marked with "LV" and a symbol showing a red spark in a white-edged blue triangle
- 182 LVMS mounted on a red circular area on high contrast background
- 183 Circular area diameter ≥ 50 mm
- 184 TSMS marked with "TS" and triangle with black lightning bolt on yellow background
- 185 TSMS mounted on an orange circular area on high contrast background
- 186 Circular area diameter ≥ 50 mm

MEASURING POINTS

- 187 Two TS measuring points on exclusive orange background
- 188 A black LV ground measuring point installed
- 189 Next to the master switches
- 190 4 mm shrouded banana jacks
- 191 Non conductive cover
- 192 Cover removable without tools
- 193 Correctly marked ("TS+", "TS-", "GND")

FORMULA STUDENT INSPECTION SHEET

ELECTRIC – copy for Formula Student Austria



TS SHUTDOWN DEVICES

- 194 Two shutdown buttons installed next to the main hoop, right and left on the vehicle at approx. height of the driver's head. Push-Pull or Push-Rotate-Pull functionality. Must be red
- 195 Marked with red spark sticker
- 196 Diameter >39 mm
- 197 One cockpit shutdown button installed. Push-Pull or Push-Rotate-Pull functionality. Must be red
- 198 Marked with red spark sticker
- 199 Easy actuation by the driver
- 200 Diameter \geq 24 mm
- 201 Inertia switch upright and rigidly mounted to the chassis and can be demounted for functionality test
- ▶ Check interlocks on ...
- 202 TS accumulator container(s)
- 203 Inverters
- 204 HVD
- 205 Power distribution boxes
- 206 Data Logger box
 - Outboard wheel motors ...
- 207 ... have a dedicated interlock wire routed along the TS wiring, must act before the TS wiring or its clamping fails
- 208 ... have a dedicated interlock wire routed along a suspension member, must act if the suspension fails
- 209 ... interlock(s) can be opened for demonstration

COCKPIT INDICATORS

- AMS indicator light ...
- 210 ... is inside the cockpit and marked with "AMS"
- 211 ... is illuminated red and visible in bright sunlight, even from outside
- 212 ... is visible for the driver
 - IMD indicator light ...
- 213 ... is inside the cockpit and marked with "IMD"
- 214 ... is red and visible in bright sunlight, even from outside
- 215 ... is visible for the driver
 - TS off indicator light ...
- 216 ... is inside the cockpit and marked with "TS off"
- 217 ... is green and visible in bright sunlight
- 218 ... is visible for the driver

TS VOLTAGE

- ▶ Measure voltage at TS measuring points
- 219 Equal or less than 60 VDC

TS WIRING

- 220 All TS wiring and components have to be in the envelope and behind the impact structures
- 221 TS cannot be activated if TS connectors outside of enclosures are connected other than the design intent configuration
- 222 TS wires of outboard wheel motors must not be able to reach the cockpit opening in case of a wire break. The wiring outside of the impact structure is the shortest possible distance.
- 223 All TS wires and connectors have proper overcurrent protection
- 224 TS wiring channels are orange
- 225 No other wires than TS wires are orange
- 226 TS wiring outside electrical enclosures in separate non-conductive conduit or orange shielded cable
- 227 Securely anchored to withstand at least 200N, if outside of enclosure
- 228 Located out of the way of possible snagging or damage
- 229 Shielded against rotating/moving parts
- 230 No wire lower than the chassis
- 231 TS and LV wires separated (n/a for interlock)
- 232 Possible to clearly assign and prove gauge, temperature, and voltage rating of TS wires
- 233 Suitable temperature rating for used position
- 234 Positive locking mechanism on every screwed connection. (Photographs for all inaccessible TS connections)
- 235 TSMPs: positive locking mechanism on every connection. (Photographs for all inaccessible TS connections)
- 236 Insulation is not insulating tape or rubber-like paint

DATA LOGGER

- 237 Data logger is fully enclosed in a housing
- 238 Data logger is rigidly mounted
- 239 Only the two preapplied 3M™ Dual Lock™ strips on the bottom side of the data logger are used
- 240 All energy from accumulator flows through the data logger

TRACTIVE SYSTEM PROTECTIONS

- ▶ Check openings in TS enclosures, try to reach TS potentials with insulated test probe (100 mm length, 6 mm diameter)
- 241 Not possible to reach any TS potentials
- 242 TS components and containers protected from moisture

HV WARNING STICKERS

- ▶ Check for warning stickers on TS containing enclosures. (triangle with a black lightning bolt on yellow background)
- 243 Inverter(s)
- 244 Motor(s)
- 245 Power Distribution box(es)
- 246 Energy meter box
- 247 Other TS containing enclosures

FORMULA STUDENT INSPECTION SHEET

ELECTRIC – copy for Formula Student Austria



HIGH VOLTAGE DISCONNECT

- 248 Clearly marked with "HVD"
- 249 Distance to ground greater than 350 mm
- 250 Inside roll-over protected envelope
- 251 No remote actuation (e.g. through wires)
- 252 Integrated interlock
 - ▶ Stand next to the vehicle, remove HVD
- 253 Removed within 10 s without tools
- 254 TS protection still given (insulated test probe). If a dummy connector is used, it must be stored at the push bar.

TRACTIVE SYSTEM ACTIVE LIGHT

- 255 Max. 75 mm below the highest point of the main hoop and within the roll-over protected envelope (including mounting) from TSAL (1.6 m eye height)
- 256 Full illuminated surface visible by a person standing 3 m away
- 257 $\leq 10^\circ$ blocked by main hoop

FIREWALLS

- Separates any point of the driver (less than 100 mm above the bottom of the helmet of the tallest driver) from any TS component (including TS wiring) . . .
- 258 . . . behind the driver's back
- 259 . . . at the sides of the driver
- 260 . . . at the front of the vehicle
- 261 First layer, facing TS must be made of Aluminum with a thickness of at least 0.5 mm
- 262 Second layer, facing driver must be made of electrically insulated material (no CFRP)
- 263 Material meets UL94-V0 for min. used thickness or equivalent
- 264 TSAC cooling duct openings do not point towards the driver, although if behind a firewall

ACCELERATOR PEDAL POSITION SENSOR (APPS)

- 265 Returns to the original position if not actuated
- 266 At least two sensors with different, non-intersecting transfer functions, with either different gradients and/or offsets to the other(s) are installed. (For digital sensors, a checksum is necessary)
- 267 Sensors are protected from being mechanically overstressed (positive stop of the pedal)
- 268 Minimum two springs installed to return pedal
- 269 Each spring still returns pedal with the second one disconnected (springs in the torque encoders not counted)

BRAKE LIGHT

- 270 Only one brake light in red color
- 271 Located on vehicle centerline, height between wheel centerline and drivers shoulder
- 272 Round, triangle, or rectangular on black background
- 273 15 cm^2 minimum illuminated area *OR* LED strips with a total length greater than 150 mm with elements <20 mm apart

ACCUMULATOR MANAGEMENT SYSTEM

- ▶ Disconnect TS accumulator
- ▶ Ask the team to connect their laptop to the AMS
- 274 AMS indicator light is illuminated red
- 275 AMS data can be displayed

FORMULA STUDENT INSPECTION SHEET

ELECTRIC – copy for Formula Student Austria



GROUNDING CHECKS

- EV 3.1 has been fully revised. Each TS enclosure must either contain a ≥ 0.5 mm properly grounded conductive layer or all materials must be electrically isolating for each own. Conductive seat, driver harness, and firewall mountings, as well as TS firewalls and conductive parts protruding through TS enclosures, must be properly grounded. A conductive part having ≤ 300 m Ω measured at 1 A and being able to continuously carry $\geq 10\%$ of the TS main fuse to LVS ground is properly grounded. Other conductive parts within 100 mm of any TS component must be ≤ 100 Ω to LVS ground.
 - It is possible to join two TS enclosures one following EV 3.1.1 point 1 and the other one following EV 3.1.1 point 2 if each individual TS enclosure is fully closed.
 - ▶ Check for each TS enclosure ...
- 276 ... all materials used to build a TS enclosure separately have a resistance ≥ 2 M Ω @ 500 V \Rightarrow fully isolated TS enclose, no grounded layer needed
- 277 ... expect e.g. screws, (shielded) connectors, backing plates isolating materials used \Rightarrow fully isolated TS enclose, no grounded layer needed but protruding elements must be properly grounded
- 278 ... at least one material has < 2 M Ω \Rightarrow ≥ 0.5 mm thick solid grounded layer made of aluminium or better required and properly grounded
- 279 ... a ≥ 0.9 mm thick steel layer might be used for TSAC as the grounded layer
- ▶ Measure resistance of conductive parts to LVS ground next to TSMPs (max. 300 m Ω @ 1 A) ...
- 280 ... main hoop
- 281 ... seat mounting points
- 282 ... driver harness mounting points
- 283 ... firewall mounting points, also if not protruding through the firewall
- 284 ... TS firewall
- 285 ... TS accumulator container
- 286 ... TS enclosures if applicable
- 287 ... TS enclosure protruding parts if applicable
- 288 Each grounding is able to carry $\geq 10\%$ of TS main fuse
- ▶ Measure resistance of conductive parts to LVS ground (max. 100 Ω @ 0 A) ...
- 289 ... carbon fiber part within 10 cm around TS part
- 290 ... suspension front left or right if applicable
- 291 ... suspension rear left or right if applicable

DIS-CHARGE CIRCUIT AND BODY PROTECTION RESISTORS

- ▶ Switch off LV. Measure resistance between TS+ and TS- measuring points
- 292 Resistance is 30 k Ω ⁸ + discharge resistor
- 293 Body protection resistor power rating is > 6.1 W⁹
- 294 Dis-charge power rating is sufficient for continuous dis-charge

INSULATION MEASUREMENT TEST

- ▶ Choose test voltage to 500 V.¹⁰
 - ▶ Connect insulation tester to TS+ and LVMP
 - ▶ Measure resistance: $R_{iso+} =$ k Ω
- 295 Resistance is much higher than 315 k Ω ¹¹
- ▶ Connect insulation tester to TS- and LVMP
 - ▶ Measure resistance: $R_{iso-} =$ k Ω
- 296 Resistance is much higher than 315 k Ω ¹¹
- 297 Resistances are nearly equal

⁸ 2 x Body Protection Resistor (BPR)

⁹ sufficient to short circuit TS+ and TS-

¹⁰ $U_{max} \leq 250 V_{DC}$ $U_{max} > 250 V_{DC}$
 $U_{Test} = 250 V_{DC}$ $U_{Test} = 500 V_{DC}$

¹¹ Minimal Resistance = 500 $\Omega/V \cdot U_{max} + BPR$

FORMULA STUDENT INSPECTION SHEET

ELECTRIC – copy for Formula Student Austria



!! TEST AT HIGH VOLTAGE !!

TRACTIVE SYSTEM POWER-UP

- ▶ All driven wheels are off the ground, driven wheels removed
- ▶ Connect multimeter between TS+ and TS-
- ▶ Switch on TSMS with LVMS deactivated
- 298 Voltage at TS measurement points less or equal 60 VDC
 - ▶ Switch on LVMS with TSMS deactivated
- 299 IMD and AMS and TS Cockpit indicator light illuminate for 1 s to 3 s for visible check
- 300 Voltage at TS measurement points less or equal 60 VDC
 - ▶ Switch on TSMS and all shutdown buttons
 - ▶ Reset any IMD or AMS errors
- 301 TS still deactivated
 - ▶ Activate TS, measure TS voltage during TS power-up. Use the team's multimeter and test leads. Set multimeter into manual range
- 302 System is precharged before second AIR closes
 - ▶ Switch off TSMS
- 303 TS voltage decreases below 60 VDC within 5 s
 - ▶ Try to power-up TS with switched off TSMS
- 304 TS still deactivated
 - ▶ Switch on TSMS
- 305 TS still deactivated

TRACTIVE SYSTEM SHUTDOWN

- ▶ Connect multimeter between TS+ and TS-
- ▶ For each of the following switches, deactivation leads to TS shutdown, the voltage decreases below 60 VDC within 5 s
- 306 LVMS
- 307 Shutdown button left
- 308 Shutdown button right
- 309 Cockpit shutdown button
- 310 Inertia switch
- 311 Break-over-travel-switch
 - ▶ Show schematic of TS with all interlocks (ESF)
- 312 Interlocks

TRACTIVE SYSTEM ACTIVE LIGHT

- ▶ Activate LVS
- 313 TSAL and Cockpit Indicator (CI) is green only
 - ▶ Activate TS
- 314 TSAL flashes red with freq 2 Hz - 5 Hz, and CI is off
- 315 TSAL is clearly visible (horizontal position, entire illuminated surface)
 - ▶ Deactivate TS, disconnect TSAC state detection circuitry connector if applicable¹², activate LVS and TS
- 316 TSAL flashes red and CI is off
 - ▶ Deactivate TS, reconnect TSAC state detection, connect power supply >60 VDC¹³ to TS¹⁴, activate LVS
- 317 TSAL is both green and red flashing simultaneously and CI is on
 - ▶ Disconnect power supply, remove HVD, override HVD interlock (!! cover TS potentials !!), activate LVS and TS
- 318 TSAL and CI is off

INSULATION MONITORING DEVICE

- 319 One IMD ground line is connected to the accumulator container¹⁵ and one ground line is connected to the main hoop by a separate wired connection
 - ▶ $R_{Test} = 135 \text{ k}\Omega$ ¹⁶
 - ▶ Activate TS, connect R_{Test} between TS+ and LV GND
- 320 Shutdown circuits opens within 30 s
- 321 IMD indicator light illuminates
- 322 TS voltage decreases below 60 VDC within 5 s after shutdown circuit opens
 - ▶ Try to activate the TS by the required additional action (EV5.11.2)
- 323 Reactivation of TS is not possible
 - ▶ Push the reset button which is not accessible to the driver, if any and/or restart LVMS
- 324 Reactivation of TS is not possible
 - ▶ Remove R_{Test} . Wait for 40 s until IMD resets status output
- 325 Reactivation of TS is not possible
 - ▶ Push all reset buttons in the cockpit, if any
- 326 Reactivation of TS is not possible
 - ▶ Push the IMD reset button which is not accessible to the driver, if any
- 327 Reactivation of TS is possible
 - ▶ Push *and hold* the reset button which is not accessible to the driver, if any. Connect R_{Test} between TS- and LV GND
- 328 Shutdown circuits opens within 30 s
- 329 IMD indicator light illuminates

¹²Skip test if disconnecting the connector also opens the interlock and/or stops LVMS supply

¹³ V_{AC} equal 42.5 V_{DC} when the signal is sinusoidal

¹⁴Do not use measuring points. The team needs to provide a method of connection that

uses the same receptacles as used for TSMP

¹⁵or the IMD's enclosure

¹⁶ $R_{Test} = (\text{max. TS voltage} \cdot 250 \text{ Ohm/V}) - \text{BPR}$

FORMULA STUDENT INSPECTION SHEET

ELECTRIC – copy for Formula Student Austria



READY TO DRIVE ACTIVATION SEQUENCE

- ▶ Activate TS, press torque pedal
- 330 No turning of motors
- ▶ Let the team set the vehicle to ready-to-drive mode
- 331 Pressing brake pedal WHILE activating is necessary
- ▶ Repeat the activation sequence, but push the brake pedal only once before finally pushing the activation button
- 332 No ready-to-drive mode possible
- ▶ Disconnect the brake sensor
- 333 No ready-to-drive mode possible
- 334 Ready to drive sound duration is 1 s to 3 s continuously
- 335 Ready to drive sound is min 80 dBA (2m around the vehicle)
- 336 Ready to drive sound is easily recognizable

APPS AND BSPD

- ▶ Set vehicle to ready to drive state
- ▶ Disconnect $\geq 50\%$ of APPS
- ▶ Move the accelerator pedal over the entire pedal travel
- 337 Motors do not turn
- ▶ Disconnect all APPS
- ▶ Move the accelerator pedal over the entire pedal travel
- 338 Motors do not turn
- ▶ Team simulates 5 kW power (complete BSPD circuitry must be used), press brake representing hard braking (>0.5 s)
- 339 TS shuts down
- ▶ Reactivate TS. Disconnect the current sensor, press brake representing hard braking (>0.5 s)
- 340 TS shuts down
- 341 Reactivation of TS is only possible after 10 s without implausibility

SEALING OF COMPONENTS

- ▶ After all tests have been passed successfully seal the inspected TS housings:
- 342 Motor Controller housing
- 343 Energy Meter housing
- 344 IMD housing
- 345 TSAL circuitry housing
- 346 BSPD casing /BSPD calibration
- 347 Additional Part:
- 348 Additional Part:

DATA LOGGER

- 349 Check data logger functionality and connectivity

SCRUTINEERING STATUS UPDATE

- ▶ Set online scrutineering status to *Passed* or *Failed*

NON-COMPLIANCE / COMMENTS

APPROVAL

Inspector Names	Date, Time	Signatures when passed
1. _____ / _____	_____	_____
2. _____ / _____	_____	_____

FORMULA STUDENT INSPECTION SHEET

ELECTRIC – copy for Formula Student Austria



PART VI: MECHANICAL INSPECTION

The time limit for this part of the inspection is 75 minutes. Continuation of the inspection is possible after requeueing. During technical inspection all work carried out on the vehicle must be approved by a technical inspector.

VEHICLE WITH TALLEST DRIVER READY TO RACE

- 350 ○ **PUSH BAR (red color)** - Securely attached to vehicle, detachable, push & pull function for 2 people. University must be written on. Two pair of HV gloves in protecting case and multimeter must be installed. The inspection sheet must always stay with the push bar.
- 351 △ **CAMERAS** - Must be secured by two points, see T13.5. No cameras mounted to helmet.
- 352 ○ **VISIBILITY** - Minimum of 100 deg. field either side. Head rotation allowed or mirrors. If mirrors, must be firmly installed and adjusted.
- 353 △ **VEHICLE CONTROLS** - All controls, including shifter, must be inside cockpit. No arms or elbows outside the SIS plane.
- 354 ○ **DRIVER FLUID PROTECTION** - A firewall (or heat resistant cover plate for cooling systems using plain water (except wheel motors and their cooling hoses)) must be rigidly mounted and extend sufficiently far upwards and/or rearwards such that any point, less than 100 mm above the bottom of the helmet of the tallest driver, is not in direct line of sight with any of the following parts: cooling system and low voltage battery.
- 355 ○ **ROLL BAR PADDING** - Roll bar or bracing that could be hit by driver's helmet must be covered with 12 mm thick, SFI spec 45.1 or FIA 8857-2001 padding.
- 356 △ **OTHER SIDE TUBES** - Design prevents driver's neck hitting bracing or other side tubes.
- 357 ○ **HEAD RESTRAINT** - Near vertical. Must take 890 N load. 40 mm thick, SFI 45.2 standard. Max. 25 mm from helmet. Helmet contact point 50 mm min. from any edge. May be changed for different drivers. Minimum 150x150 mm.
- 358 △ **SUSPENSION** - Fully operational with dampers front and rear; 50 mm minimum wheel travel (minimum jounce of 25 mm) with driver in vehicle.

VEHICLE WITHOUT DRIVER

- 359 △ **TECH STICKER SPACE** - 150 mm x 100 mm on centerline of front of vehicle in front of the cockpit opening
- 360 △ **SCHOOL NAME & OTHER DECALS** - School name, or recognized initials - min. 50 mm tall (all letters). on both sides in roman letters. Must be clearly visible.
- 361 △ **VEHICLE NUMBERS** - On front & both sides of vehicle, minimum 150 mm tall, 20 mm stroke & spacing, 25 mm min. between number and background edge, black on white, white on black only, specified background shapes. Must be clearly visible, font: Roman Sans-Serif characters.
- 362 △ **BODYWORK EDGES** - edges that could contact a pedestrian must have a minimum radius of 1.0 mm (safety requirement).
- 363 △ **BODY & STYLING** - Open wheeled, open cockpit, formula style body. Vertical keepout zones 75 mm in front and behind tires (no aero exceptions), tires unobstructed from sides.
- 364 ○ **BODYWORK** - Min. 38 mm radius on nose. No large openings in bodywork into driver compartment in front of or alongside driver, (except cockpit opening). In any side view in front of the cockpit opening no external concave radii (exception T8.2).
- 365 ○ **AERODYNAMIC DEVICES** - Securely mounted. The deflection may not exceed 10 mm when a force of 200 N is applied over a surface of 225 cm² and not more than 25 mm when a point force of 50 N is applied.
- 366 △ **AERODYNAMICS** - ALL aerodynamic devices maximum 250 mm rearward of rear tires, maximum 700 mm forward of front tires. Devices lower than 500 mm from the ground rearward of the front axle must be no wider than vertical plane from the outside of the front and rear tires. Devices higher than 500 mm behind the front axle must not be wider than the inside of the rear tires.
- 367 △ **AERO VERTICAL HEIGHT** - Devices forward of a vertical plane through the rearmost portion of the front face of the driver head restraint support, excluding any padding, set to its most rearward position, must be lower than 500 mm from the ground. Rear device max 1.2 m above ground (incl. end plates); Front device max 250 mm above ground outside of the inside plane of the front tires inside this plane max 500 mm.
- 368 ○ **EDGES/RADII** - Edges that could contact a pedestrian must have a minimum radius of: forward facing edges min 3 mm; all other edges min. 1 mm.
- 369 △ **SEAT** - Insulated against heat conduction, convection and radiation. Lowest point no lower than top of the upper surface of the lowest SIS member OR must have longitudinal, 25.4 x 1.65 mm steel tube underneath.
- 370 ○ **COCKPIT OPENING** - Fig. 11 (left) template passes down from above cockpit to below the upper side impact member. Steering wheel, seat & padding can be removed. No removing of firewall.
- 371 ○ **COCKPIT INTERNAL CROSS SECTION** - Fig. 11 (right) template passes from the cockpit opening to 100 mm rear of rearmost pedal contact area (in most forward position). Steering wheel and paddings can be removed (without tools).
- 372 △ **STEERING WHEEL** - Continuous perimeter, near round (no concave sections) with driver operable quick disconnect. 250 mm max from front hoop.
- 373 ○ **ROTATING PARTS** - Finger guards are required to cover any parts (e.g. fans) that spin while the vehicle is stationary. No holes >12 mm dia.

REMOVE BODY PANELS

- 374 ○ **JACKS** - Up to two devices that lift up all driven wheels min. 100 mm above the ground. In lifted position it is safe to enter and exit the vehicle and the devices must not extend out of the vehicles projected surface area. University name must be written on. Vehicle pickup points must be indicated by orange triangles.
- 375 ○ **DRIVER'S LEG PROTECTION** - Covers inside of cockpit over any sharp edges or moving suspension / steering components.
- 376 ○ **DRIVER'S FOOT PROTECTION** - Feet must be rearward of the front bulkhead. The front bulkhead, together with the AIP, must cover the driver's feet in front view. No part of shoes or legs above or outside the primary structure (25x1.2 or equivalent) in side or front views when touching the pedals.
- 377 ○ **PERCY** - Helmet of 95th percentile male (PERCY) including 50 mm clearance must be below the lines between top of front and main roll hoops and between top of main hoop to rear attachment point of main hoop bracing. Center of bottom circle placed minimum 915 mm from pedals.
- 378 ○ **BRAKES** - Dual hydraulic system & reservoirs, operating on all four wheels, (one brake on limited slip differential is OK). System must be protected by structure or shields from drivetrain failure or minor collisions. No plastic brake lines. No brake-by-wire. No parts below chassis in side view. Brake pedal capable of 2000 N, no failures if official exerts max force (seated normally in vehicle).

FORMULA STUDENT INSPECTION SHEET

ELECTRIC – copy for Formula Student Austria



- 379 **△ BRAKE OVER TRAVEL SWITCH** - In the event of a failure in one or both of the brake circuits the brake pedal over travel will result in the shutdown circuit being opened.
- 380 **○ WHEELS** - 203.2 mm (8") min. diam. No aluminium or hollow wheel bolts. Single retaining nut must incorporate a device to retain the nut. Aluminum wheel nuts must be hard anodized.
- 381 **○ FIREWALL** - Fire resistant material; must separate driver compartment from cooling, oil system & LV battery. Pass-throughs OK with grommets. Multiple panels OK if gaps

sealed. No gaps at sides or bottom. Must be rigidly mounted to the chassis. Material must meet UL94-V0, FAR25 or equivalent. On tractive side min. 0.5 mm aluminium plate grounded, on the driver side a rigid insulating layer (no CFRP) UL94-V0 or equivalent should be installed that can withstand a 250 N 4 mm screwdriver penetrating test.

- 382 **△ If an Autonomous System or parts thereof are present** - The ASMS must be switched off and "locked out" or "tagged out" at all times. The ASB must be deactivated/discharged. Rules 2022/T14.7 apply

VEHICLE LIFTED AND WHEELS REMOVED

- 383 **○ FASTENERS** - Steering, braking, harness and suspension systems must use SAE grade 5 or metric grade M8.8 or higher specs (AN/MS) with visible positive locking mechanisms, no adhesive or lock washers. Minimum of 2 exposed threads with lock nuts. Rod ends in single shear are captured by a washer larger than the ball diameter. Adjustable tie-rod ends must have jam nuts to prevent loosening. No nylon lock nuts for brake calipers or brake discs. No button head cap, pan head or round head screws in critical locations, e.g cage structure or harness mount. Primary structure $e/D > 1.5$. Snap or retaining rings must not bear any load in non-OEM application (e.g. not for brake disc floaters).
- 384 **○ STEERING** - All steerable wheels must have positive stops placed on the rack to prevent linkage lock up or tires from contacting any part of the vehicle. Stationary parts within rollover protection envelope. 7 degrees max. free play at the steering wheel. NO STEER-BY-WIRE on front wheels. Rear wheel steering, max. 6 deg. and mechanical stops installed. Bonded joints in accordance with T3.2.8.
- 385 **△ FLOOR CLOSEOUT PANEL** - Required from foot area to firewall; solid, non-brittle material; multiple panels are OK if gaps less than 3 mm.
- 386 **○ GAS CYLINDERS LOCATION** - Axis not pointed at driver, within the rollover protection envelope (see FIGURE 2), insulated from any heat source, must be shielded from the driver. The shields must be steel or aluminum with a minimum thickness of 1 mm.
- 387 **○ GAS CYLINDERS** - Proprietary manufacture & labeled, non-flammable gas, regulator on tank, securely mounted, appropriate lines & fittings. Positively retained, i.e. no tie-wraps. Maximum of 10 bar allowed, except cylinders/tanks with directly mounted pressure regulator (-> 10 bar).
- 388 **○ SCATTERSHIELDS INCL. MOUNTING** - Required for clutches, chains, belts, etc. No holes. 6 mm diam. grade 8.8 minimum. End parallel to lowest part of the sprocket/pulley in front and rear.
- 389 **△ SCATTERSHIELD MATERIALS** - For chains, 2 mm min. thick solid STEEL, 3 x chain width. For belts, 3 mm min. thick Al 6061-T6, 3 x belt width. Finger guards: cover all drivetrain parts that spin while vehicle is stationary. No holes >12 mm dia.
- 390 **○ LV BATTERY** - Attached securely to frame or chassis.
- 391 **○ HIGH PRESS HYDRAULICS** - Pumps and lines must have 1 mm steel or aluminium shields protecting driver and workers.

- 392 **△ COOLANT** - 100% water. NO ADDITIVES WHATSOEVER or oil for electric motors.
- 393 **○ CATCH TANKS** - Any coolant overflow or lube system vents must have separate catch tanks. 0.9 l minimum each, 100 deg. C material, behind firewall, below shoulder level. 3 mm min. dia. vent away from driver down to the bottom level of frame. Cooling systems using plain water, unless sealed, require 100 ml catch tanks.
- 394 **△ FLUID LEAKS** - Oil, grease, coolant, Brake fluid -> none permitted
- 395 **○ BELLYPANS** - In total minimum of two venting holes of at least 25 mm diameter in the lowest part of the structure to prevent accumulation of liquids. One in each enclosed chassis structure. Additional holes are required when multiple local lowest parts exist in the structure.
- 396 **○ ACCUMULATOR CONTAINER POSITION** - All accumulator containers must lie within the primary structure of the frame lower than the top of the SIS. All accumulator containers must be protected from side, rear and front impact collisions. If an accumulator container or parts of it are mounted outside of the primary structure (EV.3.5.1, EV 3.5.3) an additional impact structure according to T3.15 must be built to protect the accumulator.
- 397 **○ ACCUMULATOR CONTAINER ATTACHMENT** - Accumulator container must be attached to the primary structure with fasteners min. grade 8.8. Fasteners have to follow T10. Mounting as designed in SES. Brackets 1.6 mm steel or 4 mm aluminium with gussets to withstand bending loads. Monocoque needs 2 mm steel backing plates with perimeter near circular or oval. Equivalent attachment may be according to SES.
- 398 **○ POSITION OF TRACTIVE SYSTEM PARTS** - All parts belonging to the tractive system must be located within the rollover protection envelope, excluding outboard motors.
- 399 **○ PROTECTION OF TRACTIVE SYSTEM PARTS** - If tractive system parts are mounted in a position where damage could occur from a rear or side impact (below 350 mm from the ground), they have to be protected by a fully triangulated structure with tubes of a minimum outer diameter of 25.4 mm and a minimum wall thickness of 1.25 mm or equivalent.
- 400 **○ MOTOR CASING** - Min. 2 mm aluminium 6061-T6. May be split into two equal sections. If motor casing is rotating around the stator or is perforated an additional 1 mm aluminium 6061-T6 scatter shield around the motor should be installed.

SCRUTINEERING STATUS UPDATE

- ▶ Set online scrutineering status to *Passed* or *Failed*

FORMULA STUDENT INSPECTION SHEET

ELECTRIC – copy for Formula Student Austria



NON-COMPLIANCE / COMMENTS

APPROVAL

	Inspector Names	Date, Time	Signatures when passed
1.	_____ / _____	_____	_____
2.	_____ / _____	_____	_____

FORMULA STUDENT INSPECTION SHEET

ELECTRIC – copy for Formula Student Austria



PART VII: TILT TEST

TILT TEST

- 401 **FLUID LEAKAGE** - No fluid spill permitted when vehicle is tilted to 60 degrees in the direction most likely to create spillage. Tanks must be filled to scribe line.
- 402 **VEHICLE STABILITY** - All wheels in contact with tilt table
- 403 **GROUND CLEARANCE** - At least 30 mm min. with driver. Active suspension in lowest position.

SCRUTINEERING STATUS UPDATE

- ▶ Set online scrutineering status to *Passed* or *Failed*

NON-COMPLIANCE / COMMENTS

APPROVAL

Inspector Names	Date, Time	Signatures when passed
1. _____ / _____	_____	_____

FORMULA STUDENT INSPECTION SHEET

ELECTRIC – copy for Formula Student Austria



PART VIII: RAIN TEST

RAIN TEST

- ▶ Apply seal sticker to all additional sealing material, that can be removed (e.g. tape, as not mentioned in IN1.5.1).
- ▶ The vehicle is lifted off the ground. Tractive system has to be active (TSAL ON)
- 404 Tractive system voltage is present at TSMPs
 - ▶ **RAIN PROOF** - No driver is allowed to sit in the vehicle during the test. Water like rain will be sprayed at the vehicle for 120 sec. Another 120 sec. of waiting without water spary.
- 405 The Insulation Monitoring Device does not react and not shut down the tractive system.
 - ▶ Connect R_{Test} between any TSMP and LVS GND.
- 406 Shutdown circuits opens within 30 s.

SCRUTINEERING STATUS UPDATE

- ▶ Set online scrutineering status to *Passed* or *Failed*

NON-COMPLIANCE / COMMENTS

APPROVAL

Inspector Names	Date, Time	Signatures when passed
1. _____ / _____	_____	_____

PART IX: BRAKE TEST

BRAKE TEST

- 407 **BRAKING PERFORMANCE** - Must lock all four wheels and stop the vehicle in a straight line at the end of an acceleration run specified by the officials without electrical braking from motors. The tractive system has to be shut down by the driver before braking. The Tractive System Active Light has to be Green during breaking or shortly after the vehicle stopped (may take up to 5 sec. after shut down).
- 408 **BRAKE LIGHT** - has to be clearly visible even in bright sunlight.

SCRUTINEERING STATUS UPDATE

- ▶ Set online scrutineering status to *Passed* or *Failed*

NON-COMPLIANCE / COMMENTS

APPROVAL

Inspector Names	Date, Time	Signatures when passed
1. _____ / _____	_____	_____